

Atom ODo6-14 Outdoor UE



INTRODUCTION

The Baicells Atom OD06-14 Outdoor User Equipment (UE) provides superior wireless access performance and comprehensive routing capabilities to bring wireless broadband data and voice services to end-users. Wireless and wired devices, including mobile phones, laptops, tablets, laptop computers, printers, and other smart devices, can access the UE simultaneously.

FEATURES

- Supports LTE TDD bands 40, 41, 42, 43, 48, and customized
- 1000 Mbps Ethernet interface
- Convenient, simple, GUI-based local and remote Web management
- Built-in bipolar directional high-gain LTE antenna
- TR069 network management protocol
- Cell lock, SIM lock, and Pin lock
- User-friendly LED indicators
- Power supply with PoE
- Pole or wall mount

BASIC SPECIFICATIONS

LTE Standard	3GPP Release 10, CAT 6/7
Ethernet LAN Port	One RJ-45 port 10/100/1000 auto-sensing, auto-MDX, PoE
LED Indicators	MIU/LTE/SIM/LAN/PWR/LTE SIGNAL
USIM	1.8V/3V 2FF
Restore Button	Tactile button. Press for at least 10 seconds to restore UE to factory settings
Power Supply	Input: Universal range 100V to 240V AC Output: PoE (24VDC, 0.5A)
Dimensions (HxWxD)	9.5 x 6 x 2 inches 241 x 154 x 50 millimeters
Weight	2 lbs (900 g)

RF SPECIFICATIONS

LTE Mode	TDD
Channel Bandwidth	5 / 10 / 15 / 20 MHz
MAX Output Power	23 dBm (± 2)/TX antenna
TXRX	1T2R / 1T4R 2T2R / 2T4R (uplink enhanced)
Frequency Bands ^a	Bands 40/41/42/43/48 and customized
Antenna Gain ^b	8 dBi @ 2.x GHz, 4 ports 11 dBi @ 3.x GHz, 4 ports
Carrier Aggregation	2CC CA

Peak Rate	DL: 220 Mbps, UL: 15 Mbps (2:7)
Modulation	UL: QPSK, 16QAM, 64QAM DL: QPSK, 16QAM, 64QAM
Receive Sensitivity	-94 dBm @ QPSK, 20 MHz, 25°C
Antenna Type	Internal directional
Polarization	±45
Antenna Efficiency	> 70%
Isolation	≤ -25dB
VSWR	≤ 2
Horizontal Beamwidth (3 dB) ^b	70 ±5° @ 3.x GHz, 4 ports
Vertical Beamwidth (3 dB) ^b	30 ±5° @ 3.x GHz, 4 ports

a: Different models support different frequencies, antennas, and Carrier Aggregation configurations.

b: The current version supports only the 2-port antenna.

SOFTWARE SPECIFICATIONS

Network Mode	NAT / Router / Bridge
IP Protocol	IPv4 / IPv6
SIM	PIN management SIM lock
Network Connection Management	Auto / Manual
LTE Scan Mode	Full band scan, frequency lock
WLAN	Wi-Fi for UE alignment
VPN	<ul style="list-style-type: none"> • L2TP L2/L3 • GRE L2/L3
NAT	<ul style="list-style-type: none"> • Port forwarding • Port trigger • DMZ • ALG
Firewall	<ul style="list-style-type: none"> • IP / MAC / URL filter • Access control • Block port scanner / SYN flood • SPI filter
Network Management	TR069
Diagnostics	<ul style="list-style-type: none"> • TCP dump • Ping • Traceroute
Maintenance	<ul style="list-style-type: none"> • Date and time setting • Reboot • Restore factory settings • Restore / back up configuration files • Firmware upgrade locally or OTA
System Logs	<ul style="list-style-type: none"> • Operating • Run-time • Filter / select / display / export

Statistics	<ul style="list-style-type: none"> • LTE status; connection, system up time • Device status • DHCP client list • Wi-Fi station list • LTE status • Firewall status
------------	--

WI-FI SPECIFICATIONS

Standard	IEEE 802.11b/g/n
Channel Bandwidth	20/40 MHz
Frequency	2.4 GHz
TXRX	1T1R
Peak Rate	<ul style="list-style-type: none"> • 802.11b: 11 Mbps • 802.11g: 54 Mbps • 802.11n: 300 Mbps
Modulation	DSSS/CCK, OFDM
Receive Sensitivity	<ul style="list-style-type: none"> • -64 dBm @ 65 Mbps, typical for 802.11n • -65 dBm @ 54 Mbps, typical for 802.11g • -76 dBm @ 11 Mbps, typical for 802.11b
Max Output Power	10 ± 3 dBm
Antenna Type	Internal omni
Antenna Gain	0 dBi

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°F to 131°F / -40°C to 55°C
Storage Temperature	-40°F to 158°F / -40°C to 70°C
Operating Humidity	5% to 95%
Ingress Protection Rating	IP65

GLOBAL PART NUMBERS

EG7010C-M1	Atom Outdoor 8 dBi UE CAT 6/7, 2T2R, Band 40/41
EG7010D-M11	Atom Outdoor 11 dBi UE CAT 6/7, 2T2R, Band 42/43/48